



BUSD25V2-1x3x Rev A Datasheet



Changelog

- BUSD25-1x3x-xx (old version): All 25 pins connected 1-to-1. Shells are isolated.
- BUSD25V2-1x3x-xx (current version): All 25 pins connected 1-to-1. Shells are also all connected.

Part Number Ordering Information



1. Connector Positions


- 25 DB25

2. Connector Genders

- 1F3M 1 Female (Socket) to 3 Male (Plug)
- 1M3F 1 Male (Plug) to 3 Female (Socket)

3. Mounting Option

- FT Rubber Feet on bottom side of PCB
- DIN DIN Rail Mounting Clips



DIN Clip Mounting Option

BUSD25V2-1x3x Stocked Part Numbers

The following part numbers represent standard options and are stocked:

- BUSD25-1F3M-FT
- BUSD25-1F3M-DIN
- BUSD25-1M3F-FT
- BUSD25-1M3F-DIN

For parts other than BUSD25V2-1x3x-*, please see the other datasheets for a list of stocked part numbers.

Notice

Winford Engineering, LLC does not authorize any of its products for use in military, medical or other life-critical systems and/or devices. Life-critical devices/systems include devices or systems which, a) are intended for surgical implantation into the body, or b) support or sustain life and whose failure to perform can be reasonably expected to result in injury. Winford Engineering, LLC products are not designed with the components required, and are not subject to the testing required to ensure a level of reliability suitable for the treatment and diagnosis of people. Winford Engineering, LLC shall not be held responsible or liable for damages or injury that occur as a result of the use of this product.